

: Jan 10, 2018

Safety Data Sheet according to Regulation (EC) No. 453/2010 Date of issue:3/1/2016 Revision date:

Version: 2.2

SECTION 1: Identification of the sub	stance/mixture and of the company/undertaking
1.1. Product identifier	
Product form	: Mixture
Product name	: Tweha Prefix X-tra A-comp
1.2. Relevant identified uses of the subs	tance or mixture and uses advised against
1.2.1. Relevant identified uses	
Industrial/Professional use spec	: Industrial For professional use only
1.2.2. Uses advised against	
No additional information available	
1.3. Details of the supplier of the safety of	data sheet
ТСВ	
Stelt 7	
NL-5521HA Eersel - HOLLAND T +31 88999 81 81	
E info@tweha.com	
1.4. Emergency telephone number	
No additional information available	
SECTION 2: Hazards identification	
2.1. Classification of the substance or m	ixture
Classification according to Regulation (EC) N	o. 1272/2008 [CLP]
Flam. Liq. 3 H226	
Skin Irrit. 2 H315	
Eye Irrit. 2 H319	
Skin Sens. 1 H317	
Aquatic Chronic 2 H411	
Full text of H-phrases: see section 16	
Classification according to Directive 67/548/E	EC [DSD] or 1999/45/EC [DPD]
Xi; R36/38	
R43	
N; R51/53	
R10	
Full text of R-phrases: see section 16	
Adverse physicochemical, human health and No additional information available	environmental effects
2.2. Label elements	
Labelling according to Regulation (EC) No. 12	272/2008 [CLP]
Hazard pictograms (CLP)	
·····	GHS07 GHS09
Signal word (CLP)	: Warning
Hazardous ingredients	 reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700), bisphenol-f type epoxy resin, oxirane, mono[(C12-14-alkyloxy)methyl] derivs.
Hazard statements (CLP)	 H315 - Causes skin irritation H317 - May cause an allergic skin reaction H319 - Causes serious eye irritation H411 - Toxic to aquatic life with long lasting effects
Precautionary statements (CLP)	: P261 - Avoid breathing vapours, gas, mist, fume, spray, dust P273 - Avoid release to the environment

11/06/2015

Safety Data Sheet

according to Regulation (EC) No. 453/2010

P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water/shower P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing P501 - Dispose of contents/container to hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation

2.3. **Other hazards**

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification according to Directive 67/548/EEC
reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight \leq 700)	(CAS No) 25068-38-6 (EC no) 500-033-5 (EC index no) 603-074-00-8	25 - 75	Xi; R36/38 R43 N; R51/53
bisphenol-f type epoxy resin	(CAS No) 28064-14-4	10 - 25	Xi; R36/38 R43 N; R51/53
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	(CAS No) 68609-97-2 (EC no) 271-846-8 (EC index no) 603-103-00-4	10 - 25	Xi; R38 R43
1,6-hexaandiol diglycidyl ether	(CAS No) 16096-31-4	5 - 10	Xi; R36/38 R43 N; R51/53
Solvent naphtha (petroleum), light arom., Low boiling point naphtha - unspecified, [A complex combination of hydrocarbons obtained from distillation of aromatic streams. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C8 through C10 and boiling in the range of approximately 135°C to 210°C (275°F to 410°F).]	(CAS No) 64742-95-6 (EC no) 265-199-0 (EC index no) 649-356-00-4 (REACH-no) 2119455851-35	1,27 - 2,413	Xn; R65
2-methoxy-1-methylethyl acetate substance with a Community workplace exposure limit	(CAS No) 108-65-6 (EC no) 203-603-9 (EC index no) 607-195-00-7 (REACH-no) 01-2119475791-29	0,127 - 0,1778	R10
Name	Product identifier	Specific cond	entration limits
reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight \leq 700)	(CAS No) 25068-38-6 (EC no) 500-033-5 (EC index no) 603-074-00-8	(C >= 5) Xi;R36/38	
Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight \leq 700)	(CAS No) 25068-38-6 (EC no) 500-033-5 (EC index no) 603-074-00-8	25 - 75	Eye Irrit. 2, H319 Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411
bisphenol-f type epoxy resin	(CAS No) 28064-14-4	10 - 25	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	(CAS No) 68609-97-2 (EC no) 271-846-8 (EC index no) 603-103-00-4	10 - 25	Skin Irrit. 2, H315 Skin Sens. 1, H317
1,6-hexaandiol diglycidyl ether	(CAS No) 16096-31-4	5 - 10	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Solvent naphtha (petroleum), light arom., Low boiling point naphtha - unspecified, [A complex combination of hydrocarbons obtained from distillation of aromatic streams. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C8 through C10 and boiling in the range of approximately 135°C to 210°C (275°F to 410°F).]	(CAS No) 64742-95-6 (EC no) 265-199-0 (EC index no) 649-356-00-4 (REACH-no) 2119455851-35	1,27 - 2,413	Flam. Liq. 3, H226 STOT SE 3, H336 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
2-methoxy-1-methylethyl acetate substance with a Community workplace exposure limit	(CAS No) 108-65-6 (EC no) 203-603-9 (EC index no) 607-195-00-7 (REACH-no) 01-2119475791-29	0,127 - 0,1778	Flam. Liq. 3, H226

Name		Product identifier	Specific concentration limits
reaction product: bisphenol-A-(epichlorhydrin), epoxy (number average molecular weight \leq 700)	/ resin	(CAS No) 25068-38-6 (EC no) 500-033-5 (EC index no) 603-074-00-8	(C >= 5) Eye Irrit. 2, H319 (C >= 5) Skin Irrit. 2, H315
Full text of R- and H-phrases: see section 16			
ECTION 4: First aid measures			
I.1. Description of first aid measures			
irst-aid measures general		er give anything by mouth to an un ce (show the label where possible)	iconscious person. If you feel unwell, seek medical).
First-aid measures after inhalation	: Allov	v victim to breathe fresh air. Allow	the victim to rest.
First-aid measures after skin contact	with occu Was	plenty of soap and water. Wash c rs: Get medical advice/attention.	aminated clothing. Rinse skin with water/shower. Wash ontaminated clothing before reuse. If skin irritation Get medical advice/attention. Specific treatment (see label). If skin irritation or rash occurs: Get medical
First-aid measures after eye contact	do. C		minutes. Remove contact lenses, if present and easy to ersists: Get medical advice/attention. Get medical
First-aid measures after ingestion	: Rins	e mouth. Do NOT induce vomiting	. Obtain emergency medical attention.
.2. Most important symptoms and effe	ects, both	acute and delayed	
symptoms/injuries after inhalation	: May	cause an allergic skin reaction.	
symptoms/injuries after skin contact	: Caus	ses skin irritation.	
Symptoms/injuries after eye contact	: Caus	ses serious eye irritation.	
.3. Indication of any immediate medic	al attentic	on and special treatment needec	1
lo additional information available			
SECTION 5: Firefighting measures			
5.1. Extinguishing media			
Suitable extinguishing media	: Foar	n. Dry powder. Carbon dioxide. W	ater spray. Sand.
Insuitable extinguishing media		ot use a heavy water stream.	
.2. Special hazards arising from the s	ubstance	or mixture	
Fire hazard		mable liquid and vapour.	
Explosion hazard		form flammable/explosive vapour-	-air mixture.
.3. Advice for firefighters	,		
Firefighting instructions		water spray or fog for cooling expo nical fire. Prevent fire-fighting wate	osed containers. Exercise caution when fighting any er from entering environment.
Protection during firefighting	: Do n	ot enter fire area without proper p	rotective equipment, including respiratory protection.
SECTION 6: Accidental release mea	asures		
.1. Personal precautions, protective e		and emergency procedures	
General measures		ove ignition sources. Use special	care to avoid static electric charges. No open flames. No
6.1.1. For non-emergency personnel			
	: Evac	cuate unnecessary personnel.	
mergency procedures			
.1.2. For emergency responders	: Equi	p cleanup crew with proper protec	tion.
6.1.2. For emergency responders Protective equipment		p cleanup crew with proper protec ilate area.	tion.
.1.2. For emergency responders Protective equipment Emergency procedures			tion.
a.1.2. For emergency responders Protective equipment Emergency procedures .2. Environmental precautions	: Vent	ilate area.	
6.1.2. For emergency responders Protective equipment Emergency procedures 6.2. Environmental precautions Prevent entry to sewers and public waters. Noti	: Vent	ilate area. ies if liquid enters sewers or public	
Protective equipment Emergency procedures	: Vent	ilate area. ies if liquid enters sewers or public leaning up	

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTIO	ON 7: Handling and storage	
7.1.	Precautions for safe handling	
Additiona	I hazards when processed	: Handle empty containers with care because residual vapours are flammable.

Safety Data Sheet

according to Regulation (EC) No. 453/2010

Precautions for safe handling	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. No open flames. No smoking. Take precautionary measures against static discharge. Use only non-sparking tools. Avoid breathing vapours, gas, mist, fume, spray, dust.
Hygiene measures	: Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.
7.2. Conditions for safe storage, includ	ling any incompatibilities
Technical measures	: Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical equipment.
Storage conditions	: Keep only in the original container in a cool, well ventilated place away from : Keep away from food, drink and animal feeding stuffs. Keep container tightly closed.
Incompatible products	: Strong bases. Strong acids.
Incompatible materials	: Sources of ignition. Direct sunlight. Heat sources.
7.3. Specific end use(s)	

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. **Control parameters**

2-methoxy-1-methylethyl acetate (108-65-6)			
EU	Local name	2-Methoxy-1-methylethylacetate	
EU	IOELV TWA (mg/m ³)	275 mg/m ³	
EU	IOELV TWA (ppm)	50 ppm	
EU	IOELV STEL (mg/m ³)	550 mg/m³	
EU	IOELV STEL (ppm)	100 ppm	
EU	Notes	Skin	

8.2. Exposure controls	
Personal protective equipment	: Avoid all unnecessary exposure.
Hand protection	: Wear protective gloves
Eye protection	: Chemical goggles or safety glasses
Skin and body protection	: Wear suitable protective clothing
Respiratory protection	: Wear appropriate mask
Other information	: Do not eat, drink or smoke during use.

9.1. Information on basic physical and	d chemical properties
Physical state	: Liquid Colour
: Colourless. Odour	:
characteristic.	
Odour threshold	: No data available
рН	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 $^{\circ}$ C	: No data available
Relative density	: No data available
Solubility	: No data available
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available

Oxidising properties	: No data available
Explosive limits	: No data available
9.2. Other information	
No additional information available	
SECTION 10: Stability and reactivity	
10.1. Reactivity	
No additional information available	
10.2. Chemical stability	
Flammable liquid and vapour. May form flammal	ble/explosive vapour-air mixture
10.3. Possibility of hazardous reactions Not established.	
10.4. Conditions to avoid Direct sunlight. Extremely high or low temperatu	res Open flame Overheating Heat Sparks
	ros. Open name. Overneaung. neat. Opans.
10.5. Incompatible materials Strong acids. Strong bases.	
10.6. Hazardous decomposition products	
fume. Carbon monoxide. Carbon dioxide. May re	-
SECTION 11: Toxicological informat	
11.1. Information on toxicological effects	
Acute toxicity	: Not classified
1,6-hexaandiol diglycidyl ether (16096-31-4)	
LD50 oral rat	2900 mg/kg
2-methoxy-1-methylethyl acetate (108-65-6) LD50 oral rat	8532 mg/kg
LD50 dermal rat	> 5000 mg/kg
LC50 inhalation rat (mg/l)	> 23,8 mg/l 6h
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
	Based on available data, the classification criteria are not met
Carcinogenicity	: Not classified Reserve an available data the classification criteria are not mat
	Based on available data, the classification criteria are not met
Reproductive toxicity	: Not classified
Specific target organ toxicity (cingle oversuure)	Based on available data, the classification criteria are not met
Specific target organ toxicity (single exposure)	: Not classified Based on available data, the classification criteria are not met
Specific torget orgen tovisity (see and	
Specific target organ toxicity (repeated exposure)	: Not classified Based on available data, the classification criteria are not met
Aspiration hazard	: Not classified
	Based on available data, the classification criteria are not met
Potential adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.
SECTION 12: Ecological information	
12.1. Toxicity	
Ecology - water	: Toxic to aquatic life with long lasting effects.

Ecology - water	. Toke to aquatic life with forg fasting effects.
1,6-hexaandiol diglycidyl ether (16096-31-4)	
LC50 fishes 1	1 - 10 mg/l
2-methoxy-1-methylethyl acetate (108-65-6)	
LC50 fishes 1	> 100 mg/l 96h
EC50 Daphnia 1	> 500 mg/l 48h
ErC50 (algae)	> 1000 mg/l 72h

Safety Data Sheet

according to Regulation (EC) No. 453/2010

12.2. Persistence and degradability	
Tweha Prefix A-comp	
Persistence and degradability	May cause long-term adverse effects in the environment.
2-methoxy-1-methylethyl acetate (108-65-6	
Biodegradation	100 % 8d
12.3. Bioaccumulative potential	
Tweha Prefix A-comp	
Bioaccumulative potential	Not established.
12.4. Mobility in soil	
No additional information available	
12.5. Results of PBT and vPvB assessm	nent
No additional information available	
12.6. Other adverse effects	
Additional information	: Avoid release to the environment
Additional information	
SECTION 13: Disposal consideration	ons
13.1. Waste treatment methods	
Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
Additional information	: Handle empty containers with care because residual vapours are flammable.
Ecology - waste materials	: Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID	
14.1. UN number					
3082	3082	3082	3082	3082	
14.2. UN proper shippin	g name	1	1		
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	Environmentally hazardous substance, liquid, n.o.s.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	
Transport document descrip			•		
UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS ; reaction product: bisphenol- A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700)(25068-38-6) CONTAINS ; bisphenol-f type epoxy resin(28064-14- 4)), 9, III, (E)	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., 9, III, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS				
14.3. Transport hazard class(es)					
9	9	9	9	9	
14.4. Packing group	· · ·	× •	~ ~		
111	111	111	111	111	
14.5. Environmental hazards					
Dangerous for the environment : Yes	Dangerous for the environment : Yes Marine pollutant : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes	

R001

Safety Data Sheet

according to Regulation (EC) No. 453/2010

14.6. Special precautions for user

14.6.1. Overland transport	
Classification code (ADR)	: M6
Special provisions (ADR)	: 274, 335, 601
Limited quantities (ADR)	: 51
Excepted quantities (ADR)	: E1
Packing instructions (ADR)	: P001, IBC03, LP01,
Special packing provisions (ADR)	: PP1
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T4
Portable tank and bulk container special provisions (ADR)	: TP1, TP29
Tank code (ADR)	: LGBV
Vehicle for tank carriage	: AT
Transport category (ADR)	: 3
Special provisions for carriage - Packages (ADR)	: V12
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV13
Hazard identification number (Kemler No.)	: 90
	90 3082
Orange plates Tunnel restriction code (ADR)	:
EAC code	: •3Z
LAC CODE	. 52
14.6.2. Transport by sea	
Special provisions (IMDG)	: 274, 335
Limited quantities (IMDG)	: 5L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: P001, LP01
Special packing provisions (IMDG)	: PP1
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T4
Tank special provisions (IMDG)	: TP2, TP29
EmS-No. (Fire)	: F-A
EmS-No. (Spillage)	: S-F
Stowage category (IMDG)	: A
14.6.3. Air transport	
PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y964
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 964
PCA max net quantity (IATA)	: 450L
CAO packing instructions (IATA)	: 964
CAO max net quantity (IATA)	: 450L
Special provisions (IATA)	: A97, A158
ERG code (IATA)	: 9L
14.6.4. Inland waterway transport	
Classification code (ADN)	: M6
Special provisions (ADN)	: 274, 335, 61
Limited quantities (ADN)	: 5L
Excepted quantities (ADN)	: E1
Carriage permitted (ADN)	: T
Equipment required (ADN)	: PP
,	

Safety Data Sheet

according to Regulation (EC) No. 453/2010

Number of blue cones/lights (ADN)	: 0
Not subject to ADN	: No
14.6.5. Rail transport	
Classification code (RID)	: M6
Special provisions (RID)	: 274, 335, 601
Limited quantities (RID)	: 5L
Excepted quantities (RID)	: E1
Packing instructions (RID)	: P001, IBC03, LP01, R001
Special packing provisions (RID)	: PP1
Mixed packing provisions (RID)	: MP19
Portable tank and bulk container instructions (RID)	: T4
Portable tank and bulk container special provisions (RID)	: TP1, TP29
Tank codes for RID tanks (RID)	: LGBV
Transport category (RID)	: 3
Special provisions for carriage – Packages (RID)	: W12
Special provisions for carriage - Loading, unloading and handling (RID)	: CW13, CW31
Colis express (express parcels) (RID)	: CE8
Hazard identification number (RID)	: 90
Carriage prohibited (RID)	: No

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no substances with Annex XVII restrictions Tweha Prefix A-comp is not on the REACH Candidate List Contains no substance on the REACH candidate list Contains no REACH Annex XIV substances

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Data sources	: REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.	
Other information	: None.	
Full text of R-, H- and EUH-phrases:		
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2	
Asp. Tox. 1	Aspiration hazard, Category 1	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2	
Flam. Liq. 3	Flammable liquids, Category 3	
Skin Irrit. 2	Skin corrosion/irritation, Category 2	
Skin Sens. 1	Sensitisation — Skin, category 1	
STOT SE 3	OT SE 3 Specific target organ toxicity — Single exposure, Category 3, Narcosis	
STOT SE 3	T SE 3 Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irrita	
H226	Flammable liquid and vapour	
H304	May be fatal if swallowed and enters airways	
H315	Causes skin irritation	

Safety Data Sheet

according to Regulation (EC) No. 453/2010

H317	May cause an allergic skin reaction	
H319	Causes serious eye irritation	
H335	May cause respiratory irritation	
H336	May cause drowsiness or dizziness	
H411	Toxic to aquatic life with long lasting effects	
R10	Flammable	
R36/38	Irritating to eyes and skin	
R38	Irritating to skin	
R43	May cause sensitisation by skin contact	
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment	
R65	Harmful: may cause lung damage if swallowed	
Ν	Dangerous for the environment	
Xi	Irritant	
Xn	Harmful	

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product